



Series #	"A" Threads	"B" Lens O.D. (front) and Mount I.D.	"C" Filter and Slip Mount O.D.	"D" Height	"E" Clear Aperture
1	M22.5 x 0.5	10.0 – 18.9mm	24.5mm	6.5mm	18.5mm
2	M30.5 x 0.5	19.0 – 26.4mm	32.5mm	7mm	26.5mm
3	M40.5 x 0.5	26.4 – 36.7mm	42.0mm	7mm	36mm
4	M46 x 0.75	32.0 – 40.9mm	48.5mm	7mm	41.5mm
5	M55 x 0.75	41.0 – 50.9mm	57.0mm	7mm	50.5mm
6	M62 x 0.75	51.0 – 57.9mm	65.0mm	8mm	57.5mm
7	M72 x 0.75	58.0 – 67.9mm	75.0mm	8mm	67.7mm
8	M82 x 0.75	68.0 – 78.9mm	85.0mm	8mm	78.8mm
9	M105 x 1.0	79.0 – 100.0mm	109.0mm	11mm	100mm

Slip Mount Assembly

A Slip Mount allows a standard threaded filter to be adapted to a lens that does not have filter threads. The Mount attaches to the outside front end of a CCTV lens with 3 set screws. Standard filters can then be threaded onto the Slip Mount. Mount position on the lens is adjustable to prevent image clipping (vignetting).

MIDOPT
 Midwest Optical Systems, Inc.
 Machine Vision Filters, Lenses and Accessories
 322 Woodwork Lane, Palatine IL 60067
 P: 847-359-3550 F: 847-359-3567
 www.midopt.com

Slip Mount

Filter Adapter Assembly
 May 28, 2009